

## Product specifications

- Artificial Intelligence
- High speed processor
- Easy and fast installation
- On board scene analysis
- Multifunctional
- Day & Night mode operation
- Data and video on demand
- Multi-focal system
- Remote alert system
- Extended Video surveillance
- Face detection

- Data provided in real time
- Sensor remote control
- 24h autonomous analysis
- Fully configurable
- No need for cabling
- Low power consumption
- Fault tolerance
- Integrated IR emitter
- Smart plug
- Friendly Design
- Plate identification

- On Request
- Storage up to 128 GB
  - Dedicated PSU

### Configuration

- Easy configuration by means of a tablet device
- Real time road scene view
- Customizable ROI (region of interest)
- Direct WiFi access
- User friendly interface

### Remote control feature

- Direct control on road map
- Sensor remote control
- Data management in real time
- Remote network configuration
- Standard data representation

### Operating conditions

- Pressure compensation
- Temperature: -20°C to +80°C
- Relative Humidity: 10% to 90%
- Rain: up to 5mm/hour

### Dimensions

- Weight: 0,8 Kg
- Dimension: 250mm x 120mm x 93mm

### Interfaces

- RJ45
- SD Card 32 GB

### Power

- 12VDC
- Min power 5W, Max power 8W

### Installation

- Min height: 6mt
- Vertical tilt: from 0° to 80°
- Horizontal pan: from 0° to 180°
- Roll: from 0° to 180°
- IR emitter LOS: up to 70 mt

### Wireless Communication

- Intra network: 2.4GHz
- Extra network: 3G/LTE

### Antennas

- 2Dbi to 5Dbi, wireless network
- 3Dbi, LTE network

### Certifications

- IP66
- CE

### Country of origin

- Italy

